



# Lowest Cost, Harsh Duty, Inductive Proximity Sensor with 360° light ring

## Features:

- M8 to M30 Models
- Extended sensing ranges from 1.5 mm to 30 mm
- 360° LED light ring indicator
- Repeat accuracy <2%
- Hysteresis 2 - 10%
- Reverse polarity protection
- Switching frequency 2000 Hz
- DC 3-/4-wire, DC 2-wire configuration
- IP 67 Enclosure
- Temperature range -25 °C to +70 °C
- Nickel-plated brass housing, plastic sensing face
- Output short-circuit protection; automatically recovers from shorted load
- Available with M12 connector or Cable

## Inductive Proximity Sensor 12mm



## The only 30mm Inductive Proximity Sensor with sensing range of 30mm

## Quick Sensing Range Table (in mm)

Sizes	Standard			Extended/Triple Sense		
	Flush	Non-Flush	Price (2mtr. Cable)	Flush	Non-Flush	Price (2mtr. Cable)
M8	2.0mm	2.5mm	See Web	4.0mm	6.0mm	See Web
M12	2.5mm	4.0mm		6.0mm	10.0mm	
M18	5.0mm	8.0mm		12.0mm	18.0mm	
M30	10.0mm	15.0mm		20.0mm	30.0mm <b>WOW!</b>	

## Quick Connect Cables



Available Quick Connect Cables include:

- Industry standard M8 and M12 screw-lock connectors
- One male and one female connector
- Axial and right-angle connector models
- 2m cable lengths
- PVC (polyvinyl chloride) jacket for typical industrial applications
- IP67 rating